



art. 1519

Short description

Top product within Archibar series, is the ARCHIBAR SL300 RGBW/FC equipped with high powerful LEDs.

Robust and reliable case, the new luminarie, IP67 rated is suitable for architectural and entertainment applications.

It has a modern and appealing style which reflect the italian design

Available in 3 different measures:

- Standard 90 cm.
- On request 60 - 120 cm.
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

Description

(standard 90cm)

• SOURCE

n. 15 RGBW-FC 20W LEDs (n.15 lenses)

Total lm: R 1400, G 2300, B 450, W 3300

Total light power: 140W

• OPTIC

ARCHIBAR SL300 RGBW/FC

25°; standard (45 mm lenses)

On request: narrow, wide, elliptic 45 mm lenses

- TILT

Manual 160°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512

- CONNECTIONS

Signal: 4pin IP 67 connector (male-female)

possibility to link up to 32 devices in chain

Available as accessories:

- Wireless DMX receiver

Main Power: 3pin IP 67 connector (male-female)

possibility to link up to 6 devices at 230V or 3 devices at 120V in chain.

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

Control panel with touch technology and led display with flip function

or by DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

ARCHIBAR SL300 RGBW/FC

Active Power factor:

PF>0.94/230VAC, PF>0.98/120VAC

Current:

0.70A@230VAC, 1.25A@120V

Power: 150W

Fuse T5A (inside fixture)

- DMX CHANNELS

9CH mode, 6CH mode, 5CH mode, 4CH mode

- PHYSICAL

WxDxH: 925 x110x93 mm (dimension of profile)

Weight: 6,7 Kg.