



art. 1517

### Short description

---

The ARCHIBAR SL100 is the base version of the new Archibar line in terms of light output and kind of LEDs used.

Available in RGBW/FC and MONOCHROMATIC light source as well as in WHITE BALANCE.

Available in 4 different measures:

- Standard 90 cm.
- On request 60 - 120 - 150 cm
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

### Description

---

(standard 90cm)

#### • SOURCE

n. 7 RGBW-FC-LEDs (n.7 lenses)

Total out lumen:

R 600, G 1000, B 180, W 1200

Total light power: 49W

#### • OPTIC

## ARCHIBAR SL100 RGBW/FC

25°; medium (38 mm lenses)

On request: narrow, wide (38 mm lenses)

- TILT

Manual 160°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512

- CONNECTIONS

Signal: 3pin IP 67 connector (male-female) cable 35cm.

possibility to link up to 32 devices in chain

Available as accessories:

- Wireless DMX receiver

Main Power: 3pin IP 67 connector (male-female) cable 40cm.

possibility to link up to 10 devices at 230V or 6 devices at 120V in chain.

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

By DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

## ARCHIBAR SL100 RGBW/FC

PF>0.94/230VAC, PF>0.99/120VAC

Current:

0.25A@230VAC, 0.45A@120V

Power: 55W

Fuse T3,15A (inside fixture)

- DMX CHANNELS

9CH mode, 6CH mode, 5CH mode, 4CH mode

- PHYSICAL

WxDxH: 944 x93x115 mm

Weight: 3,8 Kg.