



art. 1516

## Short description

---

OUT OF PRODUCTION

The ARCHIBAR ST70 RGB+W it's suitable for applications where the aim it to be seen from far.

This kind of LED strip bar is then suitable for accent lighting and is available in double light source, RGB+W and only WHITE.

Available in 4 different measures:

- Standard 90 cm.
- On request 60 - 120 - 150 cm
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

## Description

---

(standard 90cm)

- SOURCE

n. 108 RGB LEDs + n. 54 White LEDs

Total out lumen:

R 360, G 600, B 150, W 1200

Total light power: 30W

## ARCHIBAR ST70 RGB+W

- OPTIC

120°;

- TILT

Manual 160°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512

- CONNECTIONS

Signal: 3pin IP 67 connector (male-female)

possibility to link up to 32 devices in chain

Main Power: 3pin IP 67 connector (male-female)

possibility to link up to 10 devices at 230V or 6 devices at 120V in chain.

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

By DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Current:

0.38A@230VAC, 0.64A@120V

Power: 38W

Fuse T3,15A (inside fixture)

## ARCHIBAR ST70 RGB+W

- DMX CHANNELS

9CH mode, 6CH mode, 5CH mode, 4CH mode

- PHYSICAL

WxDxH: 928 x60x91,4 mm (dimension of profile)

Weight: 3,8 Kg.