

PARLED 200/WB (White Balance)



art. 1511

Short description

PARLED 200/WB is our WHITE BALANCE flood projector. Suitable for touring, tv studios, venues, theatres and generally for the entertainment market.

This fixture is wireless ready. Integral Wireless DMX control is available as an option (art. WI PCB-REC).

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

Description

- SOURCE

n. 16 (2900K) warm white LEDs

n. 16 (6000K) cool white LEDs

Total out lumen: 11.000lm (with 5.000K cool white + 3.000K warm white)

Total light power: 105W

On request:

n. 32 (3000K, 4000K, 5000K, 6000K white LEDs or red, green, blue, amber LEDs)

- OPTIC

25° standard beam (38mm lenses)

On request: narrow, wide beam (38mm lenses)

- TILT

PARLED 200/WB (White Balance)

Manual 240°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512

> Integral Wireless DMX control (receiver) is available as an option (art. WI PCB-REC)

- SETUP AND CONFIGURATION

Control panel with 4 push buttons (on the rear of the fixture)

LED display with flip function (on the rear of the fixture)

Dedicated DMX channel for white balance

DMX or automatic mode with MASTER/SLAVE function

Intelligent temperature control

Flicker free function

Smooth dimming function

Halogen simulation Remote configuration by DRS Setup device

- SAFETY

eyebolts for safety chain

- IP 20 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.95/230VAC, PF>0.98/120VAC

Current: 0.55A@230VAC, 0.95A@120V

Power: 120W

Fuse T3.15A (inside fixture)

- DMX CHANNELS

- 4 ch mode

- 2 ch mode

- 1 ch mode

- PHYSICAL

PARLED 200/WB (White Balance)

WxDxH: 330x212x364(max)mm

Weight: 6,5 Kg.