

## PARLED 100 RGBW/FC



art. 1506

### Short description

---

PARLED 100 RGBW/FC flood projector for indoor use. Suitable for touring, tv studios, venues, theatres and generally for the entertainment market.

Easy setup and configuration of the fixture by control panel with push buttons.

- Colour finishing is grey. No other colours available.

### Description

---

- SOURCE

n. 7 RGBW/FC LEDs

Total out lumen: Red 500lm, Green 820lm, Blue 150lm, White 1050lm

- OPTIC

25°; standard beam (32mm lenses)

On request: narrow, wide (32mm lenses)

- TILT

Manual 360°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512

## PARLED 100 RGBW/FC

### • CONNECTIONS

Signal: XRL 5pin (on request 3pin) male-female connector

Main Power: 3x1mm cable 1,5mt.

### • SETUP AND CONFIGURATION

Control panel with 4 push buttons (on the rear of the fixture)

LED display with flip function (on the rear of the fixture)

Remote configuration by DRS Setup device

Dedicated DMX channel for white balance

DMX or automatic mode with MASTER/SLAVE function

Intelligent temperature control

Flicker free function

Smooth dimming function

Halogen simulation

CYM emulation

### • SAFETY

eyebolts for safety chain

### • IP 20 RATING PROTECTION

### • POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.91/230VAC, PF>0.98/120VAC

Current: 0.22A@230VAC, 0.38A@120V

Power: 45W

### • DMX CHANNELS

- 9 ch mode

- 5 ch mode

- 4 ch mode

### • PHYSICAL

WxDxH: 185x140x230mm

PARLED 100 RGBW/FC

Weight: 2 Kg.