



art. 1507

Short description

PARLED 100 DRS RGBW/FC. This IP 67 flood projector, has the same features of the art. 1506 except the control panel.

Configuration of the fixture by DRS Setup device.

Can be used to decorate columns, pillars, along walkways, on patios, in steps, to highlight and to landscape details and key elements.

- Colour finishing is grey. No other colours available.

Description

- SOURCE

n. 7 RGBW/FC (20W) LEDs

Total out lumen: R 550, G 1000, B 180, W 1200

- OPTIC

25°; standard beam (32mm lenses)

On request: narrow, wide (32mm lenses)

- TILT

Manual 360°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512

PARLED 100 DRS RGBW/FC

• CONNECTIONS

Signal: 4pin IP 67 male-female connector

Main Power: 3x1mm cable 1,5mt.

• SETUP AND CONFIGURATION

Remote configuration by DRS Setup device

Dedicated DMX channel for white balance

DMX or automatic mode with MASTER/SLAVE function

Intelligent temperature control

Flicker free function

Smooth dimming function

Halogen simulation

CYM emulation

• SAFETY

eyebolts for safety chain

• IP 67 RATING PROTECTION

• POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.91/230VAC, PF>0.98/120VAC

Current: 0.22A@230VAC, 0.38A@120V

Power: 45W

• DMX CHANNELS

- 9 ch mode

- 5 ch mode

- 4 ch mode

• PHYSICAL

WxDxH: 185x140x230mm

Weight: 2 Kg.