



art. 1103

Short description

OUT OF PRODUCTION

The ARCHILED 200 DRS RGBW can be considered as a further model of the well known Archiled family.

Equipped with 24 groups of four LEDs each. Clever design and very robust case, to ensure a very long term reliability specifically for harsh environments. Excellent light output with a compact size. Ideal for outdoor permanent installations to light up the details of buildings as columns, pillars, and small surfaces.

Attrattive outlook combined with a resistant case.

CYM emulation to facilitate the replacement of traditional CYM systems.

Smooth dimming function combined with an halogen simulation functionality.

Set up configuration via remote controller.

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

Description

• SOURCE

96 (4x3W) LEDs

24 groups each one with four LEDs (RGBW)

4175 total lumen (lm: 1500 W, 800 R, 1500 G, 375 B)

85W total light power

• OPTIC

ARCHILED 200 DRS RGBW

25mm quad lenses 23°;

On request:

- 10°; quad lenses

- 40°; quad lenses

• TILT

manual 160°;

• CONTROL

Standard interface: RS-485; opto-couplet input

Protocol: USITT DMX 512

• SETUP AND CONFIGURATION

By DRS - Dmx Remote Setup Dedicated

DMX channel for white balance

DMX or automatic mode with MASTER/SLAVE function

Smooth dimming function

Halogen simulation

CYM emulation

• IP RATE

IP 66

• POWER SUPPLY

Switching power supply (universal main voltage)

Rated voltage: 100-240V~; 50-60Hz

Rated power: 90W

Rated current: 0,4A @ 230V

Active Power Factor Correction

• DMX CHANNELS

- mode 9 ch

- mode 5 ch

- mode 4 ch

• PHYSICAL

WxDxH: 327x125x343mm

Weight: 8,5 kg.