

ARCHIBAR SL200/M (Monochromatic)



art. 15181

Short description

The ARCHIBAR SL200/M it has the same shape and design of the ARCHIBAR SL300 but with less powerful LEDs. Suitable for applications where the object to lit up isn't higher then 15 meters.

This version is available in MONOCHROMATIC light source with 30 powerful LEDs.

Available in 4 different measures

- Standard 90 cm. (15 lenses)
- On request 60 - 120 - 150 cm

- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

Description

• SOURCE

n. 30 high power 5000K White LEDs (n.15 lenses)

Total out lumen: 12000lm

Total light power: 90W

On request:

3000K, 4000K, 6000K white LEDs or red, green, blue, amber LEDs

ARCHIBAR SL200/M (Monochromatic)

- OPTIC 25°; medium (38 mm lenses)

On request: narrow, wide (38 mm lenses)

- TILT

Manual 160°;

- CONTROL

None

Optional: dimmable version

- CONNECTIONS

Main Power: 3pin IP 67 connector (male-female), possibility to link up to 8 devices at 230V or 4 devices at 120V in chain.

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

Plug-in

- IP 67 RATING PROTECTION

- POWER SUPPLY Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.94/230VAC, PF>0.98/120VAC

Current:

0.60A@230VAC

Power consumption: 100W

Fuse T4A (inside fixture)

- PHYSICAL

WxDxH: 928 x110x93 mm (dimension of profile)

Weight: 6 Kg.