

## ARCHIBAR SL100/M (Monochromatic)



art. 15171

### Short description

---

The ARCHIBAR SL100/M it is equipped with 14 LEDs.

It's the basic version of the new Archibar line.

This version is available in MONOCHROMATIC PLUG-IN light source. Optional DIMMABLE version.

Available in 4 different measures:

- Standard 90 cm. (7 lenses)
- On request 60 - 120 - 150 cm
  
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

### Description

---

(standard 90cm)

- SOURCE

n. 14 (5000K) White LEDs (n.7 lenses)

Total out lumen: 5800

Total light power: 45W

On request:

## ARCHIBAR SL100/M (Monochromatic)

3000K, 4000K, 6000K white LEDs or red, green, blue, amber LEDs

- OPTIC

25°; medium (38 mm lenses)

On request: narrow, wide (38 mm lenses)

- TILT

Manual 160°;

- CONTROL

None

Optional: dimmable version

- CONNECTIONS

Main Power: 3pin IP 67 LLT connector & 19mm (male-female) cable 40cm.

- SETUP AND CONFIGURATION

Plug-in

- SAFETY

n. 2 eyebolts for safety chains

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.92/230VAC, PF>0.99/120VAC

Current:

0.25A@230VAC, 0.45A@120V

Power consumption: 52W

Fuse T3,15A (inside fixture)

- PHYSICAL

WxDxH: 944 x93x115 mm

Weight: 3,8 Kg.