

ARCHIBAR SL100/WB (White Balance)



art. 15172

Short description

The ARCHIBAR SL100/M it is equipped with 14 LEDs.

It's the base version of the new Archibar line in terms of light output and kind of LEDs used.

This version is available in MONOCHROMATIC light source.

Available in 4 different measures:

- Standard 90 cm. (7 lenses)
- On request 60 - 120 - 150 cm
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

Description

(standard 90cm)

- SOURCE

n. 7 (2900K) warm white LEDs

n. 7 (6000K) cool white LEDs

n. 7 lenses

Total out lumen: 5800

Total light power: 45W

ARCHIBAR SL100/WB (White Balance)

- OPTIC

25°; medium (38 mm lenses)

On request: narrow, wide (38 mm lenses)

- TILT

Manual 160°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512

- CONNECTIONS

Main Power: 3pin IP 67 connector (male-female) cable 40cm.

Signal: 3pin IP 67 connector (male-female) cable 35cm.

Available as accessories:

- Wireless DMX receiver

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

By DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

- IP 67 RATING PROTECTION

- DMX CHANNELS

4CH mode, 2CH mode, 1CH mode

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

ARCHIBAR SL100/WB (White Balance)

Power consumption: 52W

- PHYSICAL

WxDxH: 944 x93x115 mm

Weight: 3,8 Kg.