

T-COLOR 6C RGBWAUV black light (High Power)



art. 1607

Short description

Designed to obtain the maximum performance with a minimal amount of space.

Using 6 colours, 63 high powerful RGBW/FC LEDs + 18 PC-AMBER LEDs + 18 UV LEDs (black light), the new TURBO-COLOR 6C is the most powerful and efficient IP67 LED Lighting fixture you can find within the single head category.

The TURBO-COLOR 6C is particularly adapt for touring, tv studios, venues, theatres and generally for the architainment market.

Optional IP64 version.

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

Description

• SOURCE

n. 63 (5050-20W-RTBH) + n.18 PC-Amber + n.18 UV LEDs

Total light power: 540W

Total out lumen: R 6000lm, G 13000lm, B 2000lm, W 13000lm, A 5000lm, UV 18000mW

• OPTIC

25° (38mm lenses)

On request:

- medium, wide and narrow (38 mm lenses)

Available as accessories:

- 65° plan-filter

T-COLOR 6C RGBWAUV black light (High Power)

- Barn-door

- Anti-glare

- TILT

Manual 160°

- CONTROL

Standard interface: RS-485, optocoupled input

Protocol: USITT DMX512

- CONNECTIONS

Signal: 4pin IP 67 connector (male-female)

Optional IP64 5pin XLR connector (male-female)

Main Power: 3x1mm cable 1,5mt.

Optional IP64 Power True connector

Available as accessories:

- Wireless DMX receiver

- SETUP AND CONFIGURATION

Control panel with touch technology

Led display with flip function

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Flicker-free function

Smooth dimming function

Halogen simulation

CYM simulation

- RATING PROTECTION

IP 67

- DMX CHANNELS

- 12CH mode 1

- 12CH mode 2

- 7CH mode

T-COLOR 6C RGBWAUV black light (High Power)

- 6CH mode

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor: PF 0,95

Current: 2.5A@230VAC; Fuse T10A

Power: 560W

- PHYSICAL

WxDxH: 656x159x365 mm

Weight: 15,9 Kg.