

## T-BRIGHT PLUS RGBW/FC (High Power)



art. 1603

### Short description

---

The new T- BRIGHT family becomes smaller and powerful. Designed to minimize the dimensions of a LED lighting fixture keeping an high level of lumen package in a very compact design.

The T-BRIGHT PLUS RGBW/FC is particularly adapt for touring, tv studios, venues, theatres and generally for the architainment market.

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

### Description

---

#### • SOURCE

n. 45 RGBW-FC CREE XML High Power 16W LEDs

Total light power: 340W

Total out lumen: R 4000, G 6100, B 1200, W 8100

#### • OPTIC

Square Open 20°x30°; (38mm lenses)

On request:

- medium, narrow, wide 38mm lenses

#### • TILT

Manual 160°;

#### • CONTROL

## T-BRIGHT PLUS RGBW/FC (High Power)

Standard interface: RS-485, optocoupled input

Protocol: USITT DMX512

### • CONNECTIONS

Signal: XLR 5pin (on request 3pin) IP 64 connector (male-female)

possibility to link up to 32 devices in chain

Available as accessories:

- Wireless DMX receiver

Main Power: POWERCON 3pin IP 64 connector (male-female)

possibility to link up to 6 devices at 230V or 3 devices at 120V in chain.

### • SETUP AND CONFIGURATION

Control panel with touch technology and led display with flip function

or by DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

### • RATING PROTECTION

IP 64

### • DMX CHANNELS

- 9CH mode

- 6CH mode

- 5CH mode

- 4CH mode

### • POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor: 0,95

## T-BRIGHT PLUS RGBW/FC (High Power)

Current:

1.3A@230VAC, 3.5A@120V

Power: 310W

Fuse T8A (inside fixture)

• PHYSICAL

WxDxH: 425x159x365 mm

Weight: 9,8 Kg.