



art. 1601

Short description

OUT OF PRODUCTION (replaced by PARLED 200 PRO DRS IP67 - art. 16012)

PARLED 180 IP67 is our RGBW Full Color flood light projector.

- Compact and lightweight
- No fan, very quiet operation

Suitable for touring, tv studios, venues, theatres and generally for the entertainment market.

This fixture is wireless ready. Integral Wireless DMX control is available as an option (art. WI PCB-REC).

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

Description

• SOURCE

n. 14 RGBW Full Color LEDs supplied 600mA

Total out lumen: 7000lm

• OPTIC

20° standard beam (35mm lenses)

On request: wide beam (35mm lenses)

• TILT

PARLED 180 RGBW/FC IP67

Manual 360°;

- CONTROL

Standard interface: RS-485; opto-couplet bi-directional

Protocol: USITT DMX 512, RDM Protocol ready

- CONNECTIONS

Main Power: 3pin IP 67 connector (male-female)

> Integral Wireless DMX control (receiver) is available as an option (art. WI PCB-REC)

- SETUP AND CONFIGURATION

Dedicated DMX channel for white balance

DMX or automatic mode with MASTER/SLAVE function

Intelligent temperature control

Flicker free function

Smooth dimming function

Halogen simulation

CYM emulation

Remote configuration by DRS Setup device

- IP 67 RATING PROTECTION

- POWER SUPPLY

Switching power supply (universal main voltage)

Rated voltage: 100-240V~; 50-60Hz

Rated power: 90W

Current: 0.4A@230VAC, 0.9A@120V

- DMX CHANNELS

- 9 ch mode

- 6 ch mode

- 5 ch mode

- 4 ch mode

- PHYSICAL

WxDxH: 330x212x364(max)mm

Weight: 6,5 Kg.

