



art. 16012

Short description

PARLED 200 PRO DRS IP67 is our RGBW Full Color flood light projector.

Fixture configuration by DRS Setup.

- Compact and lightweight
- No fan, very quiet operation
- IP67 protection rating

Suitable for touring, tv studios, venues, theatres and generally for the architainment market.

This fixture is wireless ready. Integral Wireless DMX control is available as an option (art. WI PCB-REC).

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

Description

• SOURCE

n. 16 RGBW Full Color LEDs supplied 600mA

Luminous flux: Red 1500lm, Green 2200lm, Blue 450lm, White 3000lm

• OPTIC

15° beam (38mm lenses)

On request: medium and wide beam (38mm lenses)

PARLED 200 PRO DRS RGBW/FC IP67

- TILT

Manual 360°;

- CONTROL

Standard interface: RS-485; opto-couplet bi-directional

Protocol: USITT DMX 512, RDM Protocol ready

- CONNECTIONS

Signal: 4pin IP 67 connector (male-female)

possibility to link up to 32 devices in chain

Main Power: 3x1mm cable 1,5mt.

> Integral Wireless DMX control (receiver) is available as an option (art. WI PCB-REC)

- SETUP AND CONFIGURATION

Dedicated DMX channel for white balance

DMX or automatic mode with MASTER/SLAVE function

Intelligent temperature control

Flicker free function

Smooth dimming function

Halogen simulation

CYM emulation

Remote configuration by DRS Setup device

- IP67 RATING PROTECTION

- WORKING TEMPERATURE

-20°C +45°C

- POWER SUPPLY

Switching power supply (universal main voltage)

Rated voltage: 120-240V~; 50-60Hz

Rated power: 100W

Current: 0,45A@230VAC; PF 0,95

- DMX CHANNELS

- 9 ch mode

- 6 ch mode

PARLED 200 PRO DRS RGBW/FC IP67

- 5 ch mode

- 4 ch mode

• PHYSICAL

WxDxH: 305x212x364(max)mm

Weight: 6,5 Kg.