

ARCHILED 200 RGBWA



art. 1701

Short description

The ARCHILED 200 RGBWA is the last version of the Archiled range.

It's even more compact (only 100mm depth), elegant, highly reliable and even more robust from a mechanical point of view. IP 67 rating protection.

With its 16 powerfull RGBW LEDs + 10 AMBER LEDs, is particularly adapt to be used to light up with deep beam of light, several final applications in the architectural field specifically for hotels and hospitality, retail and commercial malls, parks and landscapes, historical and cultural monuments.

Touch control panel for easy configuration of the fixture.

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

Description

• SOURCE

n. 16 RGBW LEDs + n. 10 AMBER LEDs

Total lm: R 1300, G 1800, B 380, W 2500, A 1300

85W total light power

• OPTIC

15° beam (38mm lenses)

On request: narrow and wide beam (38mm lenses)

• TILT

Manual 160°

• CONTROL

ARCHILED 200 RGBWA

Standard interface: RS-485; opto-couplet bi-directional

Protocol: USITT DMX 512

> Integral Wireless DMX control (receiver) is available as an option (art. WI PCB-REC).

• CONNECTION

Main Power: 3x1 cable 1,5mt.

DMX INPUT: 4 Pin Male IP67 connector (cable 25cm.)

DMX OUTPUT: 4 Pin Female IP67 connector (cable 25cm.)

• SETUP AND CONFIGURATION

Control panel with touch technology and led display with flip function

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Flicker-free function

Smooth dimming function

Halogen simulation

CYM simulation

Remote configuration by DRS Setup device

• IP 67 RATING PROTECTION

• POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power Factor: PF>0.94

Power: 90W

• DMX CHANNELS

- 10 ch mode

- 7 ch mode

- 6 ch mode

- 5 ch mode

• PHYSICAL

WxDxH: 270x100x303 mm

ARCHILED 200 RGBWA

Weight: 4,9 kg.