

## ARCHIBAR ST80 RGBW



art. 1740

### Short description

---

The ARCHIBAR ST80 RGBW. It's suitable for applications where the aim is to be seen from far.

This kind of LED bar is suitable for accent lighting and is available in double light source, RGBW and MONOCHROMATIC.

Available in 3 different measures:

- Standard 100 cm.
- On request 50 - 150 cm
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

### Description

---

(standard 100cm)

- SOURCE

n. 28+28+28+28 Red, Green, Blue, White LEDs

Lumen:

R 460, G 950, B 260, CW 1300

Total light power: 32W

- OPTIC

120°

## ARCHIBAR ST80 RGBW

- TILT

Manual 160°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512

- CONNECTIONS

Signal: 3pin IP 67 connector (male-female) cable 35cm.

possibility to link up to 32 devices in chain

Main Power: 3pin IP 67 connector (male-female) cable 40cm.

possibility to link up to 10 devices at 230V or 6 devices at 120V in chain

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

By DRS (remote control device)

DMX or Auto mode with Master-Slave function

Halogen simulation

Flicker-free function

Smooth dimming function

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Current: 0.2A@230VAC

Power: 46W

Fuse T3,15A (inside fixture)

- DMX CHANNELS

4CH mode

- PHYSICAL

WxDxH: 1004x93x115 mm

Weight: 3,5 Kg.

