

ARCHIBAR SL150 RGBW RDM



art. 1840

Short description

The ARCHIBAR SL150 RDM is a new version of the Archibar line.

Available in RGBW/FC and MONOCHROMATIC light source as well as in WHITE BALANCE.

RDM / DMX Protocol. Configuration by DRS Setup.

Available in 4 different measures:

- Standard 90 cm.
- On request 60 - 120 - 150 cm
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

Optional: marine grade treatment.

Description

(standard 90cm)

- SOURCE

n. 12 RGBW LEDs

Total out lumen:

R 750, G 1100, B 230, W 1600

Total light power: 60W

ARCHIBAR SL150 RGBW RDM

- OPTIC

25°; medium (38 mm lenses)

On request: narrow, wide (38 mm lenses)

- TILT

Manual 160°;

- CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512 / RDM

- CONNECTIONS

Signal: 3pin IP 67 connector (male-female) cable 35cm.

possibility to link up to 32 devices in chain

Available as accessories:

- Wireless DMX receiver

Main Power: 3pin IP 67 connector (male-female) cable 40cm.

possibility to link up to 8 devices at 230V or 4 devices at 120V in chain.

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

RDM Control/configuration or individually by DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

ARCHIBAR SL150 RGBW RDM

Active Power factor:

PF>0.97@230VAC

Current: 0.2A@230VAC

Power: 45W

Fuse T3,15A (inside fixture)

- DMX CHANNELS

9CH mode, 6CH mode, 5CH mode, 4CH mode

- PHYSICAL

WxDxH: 944x93x115 mm

Weight: 4,4 Kg.