



art. 1844

Short description

The ARCHIBAR SL150 RDM is a new version of the Archibar line.

Available in RGBW/FC and MONOCHROMATIC light source as well as in WHITE BALANCE.

Standard version Plug-in.

Optional dimmable version DMX / RDM / DALI, configuration by DRS Setup.

Available in 4 different measures:

- Standard 90 cm.
- On request 60 - 120 - 150 cm
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

Optional: marine grade treatment.

Description

(standard 90cm)

- SOURCE

n. 24 (5000K) White LEDs

Total out lumen: 7500

Total light power: 48W

On request:

ARCHIBAR SL150 / M RDM

3000K, 4000K, 6000K white LEDs or red, green, blue, amber LEDs

- OPTIC

20°x30°; Square Open (38 mm lenses)

On request: narrow, medium, wide and 30°x50°; (38 mm lenses)

- TILT

Manual 160°;

- CONTROL

None

On request: dimmable version DMX / DALI

- CONNECTIONS

Main Power: 3pin IP 67 LLT connector & slash; 19mm (male-female) cable 40cm.

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

Plug-in

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.97/230VAC

Current: 0.23A@230VAC

Power: 55W

Fuse T3,15A (inside fixture)

- PHYSICAL

WxDxH: 944x93x115 mm

Weight: 3,8 Kg.