



art. 1852

Short description

The ARCHIBAR-i SL150 RDM is a new version of the Archibar line.

INGROUND LED linear bar which combines aesthetic and resistance with ideal performance in a versatile projector. Waterproof and tremendously resistant.

Available in RGBW/FC and MONOCHROMATIC light source as well as in WHITE BALANCE.

RDM / DMX Protocol. Configuration by DRS Setup.

Description

• SOURCE

n. 12 (2900K) warm white LEDs

n. 12 (6000K) cool white LEDs

Total out lumen: 6000

Total light power: 40W

• OPTIC

20°x30°; Square Open (38 mm lenses)

On request: narrow, medium, wide and 30°x50°; (38 mm lenses)

• CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512 / RDM

ARCHIBAR-i SL150 / WB RDM Inground

• CONNECTIONS

Available as accessories:

- Wireless DMX receiver

• SETUP AND CONFIGURATION

RDM Control/configuration or individually by DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

• IP 67 RATING PROTECTION

• POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

$PF \geq 0.97/230VAC$

Current: 0.19A@230VAC

Power: 45W

Fuse T3,15A (inside fixture)

• DMX CHANNELS

4CH mode, 2CH mode, 1CH mode

• PHYSICAL

WxDxH: 1063x182x133 mm

Weight: 15 Kg.