



art. 18541

Short description

The ARCHIBAR-i SL150 RDM is a new version of the Archibar line.

INGROUND LED linear bar which combines aesthetic and resistance with ideal performance in a versatile projector. Waterproof and tremendously resistant.

Available in RGBW/FC and MONOCHROMATIC light source as well as in WHITE BALANCE.

Plug-in version, available on request RDM / DMX Protocol dimmable version (art. 1854). Configuration by DRS Setup.

Description

• SOURCE

n. 24 (5000K) White LEDs

Total out lumen: 7500

Total light power: 48W

On request:

3000K, 4000K, 6000K white LEDs or red, green, blue, amber LEDs

• OPTIC

20°x30°; Square Open (38 mm lenses)

On request: narrow, medium, wide and 30°x50°; (38 mm lenses)

• CONTROL

None

ARCHIBAR-i SL150 / M Inground

On request: dimmable version RDM - DMX / DALI (art. 1854)

- SETUP AND CONFIGURATION

Plug-in

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.97/230VAC

Current: 0.19A@230VAC

Power: 45W

Fuse T3,15A (inside fixture)

- PHYSICAL

WxDxH: 1063x182x133 mm

Weight: 15 Kg.