

ARCHIBAR SL100 IC RGBW RDM (individual control)



art. 1830

Short description

Individual Control LED linear bar conceived for the architectural market. SINGLE PIXEL control to obtain astonishing effects, DMX - RDM protocol.

The ARCHIBAR SL100 IC RGBW RDM is equipped with 12 high powerful LEDs.

Robust and reliable case, IP67 protection rating, it has a compact, modern and appealing style which reflect the italian design.

Available in 2 different measures:

- Standard 100 cm. (n.12 LEDs)
- On request 50 cm. (n.6 LEDs)

- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

Description

(standard 100cm)

• SOURCE

n. 12 RGBW LEDs (individual control)

Total lm: R 500, G 800, B 180, W 1000

Total light power: 55W

• OPTIC

ARCHIBAR SL100 IC RGBW RDM (individual control)

medium beam (38 mm lenses)

On request: narrow, wide (38 mm lenses)

- TILT

Manual 160°;

- CONTROL

Standard interface: RS-485, optocoupled input

Protocol: RDM / DMX 512, ArtNet by external converter

- CONNECTIONS

Signal: 3pin IP 67 connector (male-female) cable 35cm.

possibility to link up to 32 devices in chain

Available as accessories:

- Wireless DMX receiver

Main Power: 3pin IP 67 connector (male-female) cable 40cm.

possibility to link up to 10 devices at 230V or 6 devices at 120V in chain.

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

RDM Control/configuration or individually by DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

- IP 67 RATING PROTECTION

- POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power Factor: PF>0.95

ARCHIBAR SL100 IC RGBW RDM (individual control)

Power: 80W

• PHYSICAL

WxDxH: 1020 x93x115 mm

Weight: 4,5 Kg.