

ARCHIBAR-i T SL150 RGBW RDM Inground Tilt



art. 1930

Short description

The ARCHIBAR-i T (TILT version) SL150 RDM is a new version of the Archibar line.

Motorized tilt 0-10°; by DRS Setup.

INGROUND LED linear bar which combines aesthetic and resistance with ideal performance in a versatile projector. Waterproof and tremendously resistant.

Available in RGBW/FC and MONOCHROMATIC light source as well as in WHITE BALANCE.

RDM / DMX Protocol. Configuration by DRS Setup.

Description

• SOURCE

n. 12 RGBW LEDs

Total out lumen:

R 750, G 1100, B 230, W 1600

Total light power: 40W

• OPTIC

25°; medium (38 mm lenses)

On request: narrow, wide (38 mm lenses)

• TILT

Motorized tilt from 0°; to 10°;

ARCHIBAR-i T SL150 RGBW RDM Inground Tilt

• CONTROL

Standard interface: RS-485

Protocol: USITT DMX 512 / RDM

• CONNECTIONS

Available as accessories:

- Wireless DMX receiver

• SETUP AND CONFIGURATION

RDM Control/configuration or individually by DRS (remote control device)

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Halogen simulation

CYM simulation

Flicker-free function

Smooth dimming function

• IP 67 RATING PROTECTION

• POWER SUPPLY

Voltage range: 100-240VAC

Frequency range: 47-63Hz

Active Power factor: PF>0.97 @230VAC

Current: 0.2A@230VAC

Power: 45W

Fuse T3,15A (inside fixture)

• DMX CHANNELS

9CH mode, 6CH mode, 5CH mode, 4CH mode

• PHYSICAL

WxDxH: 1063x182x133 mm

Weight: 15 Kg.