



art. 1008

### Short description

---

OUT OF PRODUCTION

The ARCHIBAR 100 DRS RGBW is a LED lighting bar for outdoor use. Belong to the ARCHIBAR family with less power. IP66 rated and hence suitable for external architectural applications. Full remote DMX set up for RGBW, to allow endless colour mixing possibilities. Dedicated DMX channel for white balance that allow the product to be also suitable for theatre and stage lighting.

- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

### Description

---

#### • SOURCE

n. 64 (4x3W) LEDs

16 groups each one with four LEDs (RGBW)

3350 total lm (lm: 1200 W, 650 R, 1200 G, 300 B)

60W total light power

#### • OPTIC

25mm quad lenses 23°;

On request:

- 10°; quad lenses

- 40°; quad lenses

## ARCHIBAR 100 DRS RGBW

- TILT

manual 120°;

- CONTROL

Standard interface: RS-485; opto-couplet input

Protocol: USITT DMX 512

- SETUP AND CONFIGURATION

By DRS - Dmx Remote Setup

Dedicated DMX ch for white balance

DMX or automatic mode with MASTER/SLAVE function

Smooth dimming function

Flicker-free function

Halogen simulation

CYM emulation

- RATING PROTECTION

IP 66

- POWER SUPPLY

Switching power supply (universal main voltage)

Rated voltage: 100-240V~; 50-60Hz

Rated power: 70W

Rated current: 0,3A @ 230V

Active Power Factor Correction

- DMX CHANNELS

- 9 ch mode

- 5 ch mode

- 4 chmode

- PHYSICAL

WxDxH: 1010x87x68mm (dimension of profile)

Weight: 8 kg.