

THEATRE 1000C PLUS RDM (Monochromatic)



art. 1862

Short description

THEATRE 1000C PLUS RDM is our new compact LED diffuser with Hi-Power strip LEDs that reproduce an Halogen linear lamp.

Dimmable DMX-RDM version with cool LEDs.

Complete with gelatin holder frame.

Standard fixture colour finishing is black. Optional: grey and white (art. FX-COLOUR).

Description

- SOURCE (cool white)

n. 19 cool 5750K White LEDs

On request: neutral or warm white, red, green, blue, amber LEDs

Total out lumen: 10.000lm

Total light power: 75W

CRI: >70

- OPTIC

110°

- TILT

Manual 240°

- CONTROL

Standard interface: RS-485/RDM, optocoupled input

THEATRE 1000C PLUS RDM (Monochromatic)

Protocol: USITT DMX512

• CONNECTIONS

Signal: IN/OUT XLR 5pin (on request 3pin) connector (male-female)

possibility to link up to 32 devices in chain

Main Power: IN/OUT POWERCON 3pin connector (male-female)

possibility to link up to 8 devices @230V or 4 devices @120V in chain

• SETUP

RDM Control/Configuration or individually by DRS (remote control device)

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Flicker-free function

Smooth dimming function

Halogen simulation

STROBE EFFECT: 0.5-25Hz

• SAFETY

eyebolts for safety chain

• WORKING TEMPERATURE

-30° +45°

• RATING PROTECTION

IP20

• POWER SUPPLY

Voltage range: 180-277VAC

Frequency range: 47-63Hz

Active Power factor:

PF>0.90@230VAC

Inrush current: 60A

Current: 0.35A@230VAC

Power consumption: 80W

• DMX CHANNELS

- 3 CH mode

THEATRE 1000C PLUS RDM (Monochromatic)

- 1 CH mode

• PHYSICAL

WxDxH: 255x225x175mm

Weight: 3 Kg.