



art. 1111

### Short description

---

#### OUT OF PRODUCTION

The ARCHIBAR 100 DRS White Balance is a LED lighting bar available with 2700 K and 6000 K white light to meet any design specification.

ARCHIBAR 100 DRS White Balance is the completion of the outdoor linear LED lighting products of the ARCHIBAR family.

The compact outline features a robust and durable extruded aluminium housing certified to an IP66 weather protection for the widest variety of applications such as facades, show lighting effect and landscape lighting.

- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

### Description

---

#### • SOURCE

n. 64 (3W) LEDs

16 groups each one with four LEDs (2 Warm White, 2 Cool White)

4000 total lm

60W total light power

#### • OPTIC

25mm quad lenses standard 23°;

On request:

- 10°; quad lenses

## ARCHIBAR 100 DRS WB

- 40°; quad lenses

- TILT

manual 120°;

- CONTROL

Standard interface: RS-485; opto-couplet input

Protocol: USITT DMX 512

- SETUP AND CONFIGURATION

By DRS - Dmx Remote Setup

Dedicated DMX channel for white balance (2700 K ... 6000 K)

DMX or automatic mode with MASTER/SLAVE function

Smooth dimming function

Flicker-free function

Halogen simulation

- RATING PROTECTION

IP 66

- POWER SUPPLY

Switching power supply (universal main voltage)

Rated voltage: 100-240V~; 50-60Hz

Rated power: 70W

Rated current: 0,3A @ 230V

Active Power Factor Correction

- DMX CHANNELS

- 4 ch mode

- 2 ch mode

- 1 ch mode

- PHYSICAL

WxDxH: 1010x87x68mm (dimension of profile)

Weight: 8 kg.