



art. 1301

Short description

PARLED 200 PRO is our IP20 RGBW Full Color flood projector with control panel (four buttons on the rear). Suitable for touring, tv studios, venues, theatres and generally for the entertainment market. Indoor use.

This fixture is wireless ready. Integral Wireless DMX control is available as an option (art. WI PCB-REC).

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

Description

• SOURCE

n. 16 (12W) RGBW Full Color LEDs supplied 600mA

8000 total lm

130W total light power

• OPTIC

20°; standard beam (35mm lenses)

On request: 40°; wide beam (35mm lenses)

• TILT

Manual 360°;

• CONTROL

Standard interface: RS-485; opto-couplet bi-directional

PARLED 200 PRO RGBW/FC

Protocol: USITT DMX 512, RDM Protocol ready

> Integral Wireless DMX control (receiver) is available as an option (art. WI PCB-REC).

• SETUP AND CONFIGURATION

Control panel with 4 push buttons (on the rear of the fixture)

LED display with flip function (on the rear of the fixture)

Dedicated DMX channel for white balance

DMX or automatic mode with MASTER/SLAVE function

Intelligent temperature control

Flicker free function

Smooth dimming function

Halogen simulation

CYM emulation

Remote configuration by DRS Setup device

• IP 20 RATING PROTECTION

• POWER SUPPLY

Switching power supply (universal main voltage)

Rated voltage: 100-240V~; 50-60Hz

Rated power: 80W

Rated current: I max 0,4A@230V - fuse T3.15A

Active Power Factor Correction

• DMX CHANNELS

- 9 ch mode

- 5 ch mode

- 4 ch mode

• PHYSICAL

WxDxH: 330x212x364(max)mm

Weight: 6,5 Kg.