

CITYBEAM LED24 RGBW/FC (High Power)



art. 1304

Short description

- 6°; narrow beam angle
- Astonishing level of brightness up to 250 meters
- High Power RGBW/FC 20W LEDs
- Energy efficient

To reach impressive heights, no matter how complex it is, the new CITYBEAM LED 24 is the right solution. Whatever is the final application, where long distance light output is required the CITYBEAM LED family solve your problem.

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

[Clic here to view the CityBeam LED 12](#)

Description

• SOURCE

n. 24 RGBW (20W) LEDs

190W total light power

Total lm: R 3000, G 5000, B 900, W 6000

• OPTIC

6°; (45 mm lenses)

• TILT

CITYBEAM LED24 RGBW/FC (High Power)

Manual 160°:

- CONTROL

Standard interface: RS-485, optocoupled input

Protocol: USITT DMX512

- CONNECTIONS

Signal: 4pin IP 67 connector (male-female)

Main Power: 3x1mm cable 1,5mt.

Available as accessories:

- Wireless DMX receiver

- SAFETY

n. 2 eyebolts for safety chains

- SETUP AND CONFIGURATION

Control panel with touch technology

Led display with flip function

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Flicker-free function

Smooth dimming function

Halogen simulation

CYM simulation

- RATING PROTECTION

IP 67

- DMX CHANNELS

- 9CH mode

- 5CH mode

- 4CH mode

- POWER SUPPLY

Voltage range: 88-264VAC, 124-370VDC

Frequency range: 47-63Hz

CITYBEAM LED24 RGBW/FC (High Power)

Active Power factor: PF>0.95/230VAC, PF>0.98/115VAC

Current: 0.9A@230VAC; Fuse T5A

Power: 210W (all color full power)

- PHYSICAL

WxDxH: 615x185x420 mm

Weight: 18,5 Kg.