

SINGLE 20 RGBW/FC (High Power)



art. 1402

Short description

The new SINGLE 20 RGBW/FC (Full Color) is a refined and compact, IP67 LED Lighting fixture with a large and uniform light output.

The fixture uses high brightness LEDs RGBW/FC and combines an innovative optic system with a wide beam for a superb color mixing.

Highly efficient and impressive light output. Suitable for permanent architectural installations and for temporarily events.

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

[Clic here to view the Single 40](#)

Description

- SOURCE

n. 20 RGBW (16W) LEDs

95W total light power

Total lm: R 1500, G 3000, B 460, White 3400

- OPTIC

medium beam (45mm lenses)

On request:

- narrow, wide beam (45 mm lenses)

- 65°: plan-filter

SINGLE 20 RGBW/FC (High Power)

- Barn-door

- Anti-glare

• TILT

Manual 160°

• CONTROL

Standard interface: RS-485, optocoupled input

Protocol: USITT DMX512

• CONNECTIONS

Signal: 4pin IP 67 connector (male-female)

Main Power: 3x1mm cable 1,5mt.

Available as accessories:

- Wireless DMX receiver

• SETUP AND CONFIGURATION

Control panel with touch technology

Led display with flip function

Dedicated DMX channel for white balance

DMX or Auto mode with Master-Slave function

Intelligent temperature control

Flicker-free function

Smooth dimming function

Halogen simulation

CYM simulation

• RATING PROTECTION

IP 67

• DMX CHANNELS

- 9CH mode

- 5CH mode

- 4CH mode

• POWER SUPPLY

Voltage range: 88-264VAC, 124-370VDC

SINGLE 20 RGBW/FC (High Power)

Frequency range: 47-63Hz

Active Power factor: PF>0.95/230VAC, PF>0.98/115VAC

Current: 0,45A@230VAC; Fuse T3.15A

Power: 105W (on white balance)

- PHYSICAL

WxDxH: 355x185x415 mm

Weight: 12 Kg.