



Studio Due®

emotion and creativity in light



Archibar SL100

The ARCHIBAR SL100 is the base version of the new Archibar line in terms of light output and kind of LEDs used. Available in RGBW/FC and MONOCHROMATIC light source as well as in WHITE BALANCE.

Available in 4 different measures:

- Standard 90 cm.
- On request 60 - 120 - 150 cm

- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

TECHNICAL FEATURES

www.studiodue.com

ITEM	FIXTURE	90cm standard	60cm	120cm	150cm
LEDs	RGBW	7 RGBW/FC	5 RGBW/FC	9 RGBW/FC	11 RGBW/FC
Total light power		49W	35W	63W	77W
Lumen		R 600, G 1000, B 180, W 1200	R 550, G 720, B 130, W 860	R 780, G 1290, B 235, W 1560	R 950, G 1580, B 285, W 1890
Optics		medium beam (38 mm lenses) - On request: narrow and wide beam			
Power consumption		55W	43W	69W	85W
Voltage range		Universal 100 - 240Vac			
Physical		944x93x115 mm	664x93x115 mm	1212x93x115 mm)	1484x93x115 mm
Weight		3,8 Kg	-	-	-

Control	Standard interface: RS-485, optocoupled input - Protocol: USITT DMX512
Connections	Signal: 3pin IP 67 connector (male-female) possibility to link up to 32 devices in chain Main Power: 3pin IP 67 connector (male-female) possibility to link up to 21 devices at 230V or 11 devices at 120V in chain.
Setup	By DRS (remote control device) Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Halogen simulation CYM simulation Flicker-free function Smooth dimming function
DMX channels	9CH mode, 6CH mode, 5CH mode, 4CH mode



