

Studio Due®

emotion and creativity in light



Inground LED fixture with powerful MONOCHROMATIC LEDs. IP67 rating protection. It is possible to adjust the TILT position of the fixture. The motorized tilt adjustment function (by dedicated DRS Setup) allows you to position the light beam in the most appropriate way, so it is not necessary to open the device that maintains the degree of protection IP67. Manual Pan 180° and motorized Tilt adjustment -2° +10°. TERRA PLUS-T RDM /WB (White Balance) and TERRA PLUS-T RDM /M (Monochromatic) can be used to decorate columns, pillars, along walkways, on patios, in steps, to highlight and to landscape details and key elements.

• Standard fixture colour finishing is grey

ITEM	FIXTURE	[KEY features]
LEDs	Monochromatic	24 warm, neutral, cool white On request: red, green, blue or amber
	White Balance	12 Cool White + 12 Warm White
Total light power		40W
Lumen		6200 (4000K LEDs)
Optics		15° beam (38 mm lenses) - On request: medium and wide beam
Pan - Tilt		Manual Pan 180° - Motorized Tilt adjustment -2°... +10° by DRS Setup (needed)
Power consumption		45W - 0,2A@230V - PF0,9
Voltage range		Universal 100 - 240Vac
Physical		DxH: ø 290x200mm
Weight		5,5 Kg
Control		Standard interface: RS-485, Protocol: RDM / DMX 512, Artnet by external converter
Connections		Main Power: 3x1 cable DMX INPUT and Tilt control: 4 Pin Male IP67 connector DMX OUTPUT: 4 Pin Female IP67 connector
Setup		RDM Control/configuration or individually by DRS (remote control device) Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Intelligent temperature control Halogen simulation CYM simulation Flicker-free function Smooth dimming function
DMX channels	Monochromatic	3CH mode, 1CH mode
	White Balance	4CH mode, 2CH mode, 1CH mode


Studio Due®

emotion and creativity in light

dedicated DRS Setup for Tilt adjustment



motorized tilt adjustment



art. 1733-1734-1735 only

