



Studio Due®

emotion and creativity in light



Archibar SL150

The ARCHIBAR SL150 RDM is a new version of the Archibar line. Available in RGBW/FC and MONOCHROMATIC light source as well as in WHITE BALANCE. RDM / DMX Protocol. Configuration by DRS Setup.

Available in 4 different measures:

- Standard 90 cm.
- On request 60 - 120 - 150 cm
- Standard fixture colour finishing is grey. Optional black and white (art. FX-COLOUR).

TECHNICAL FEATURES

www.studiodue.com

ITEM	FIXTURE	90cm standard	60cm	120cm	150cm
LEDs	RGBW	12 RGBW/FC	8 RGBW/FC	16 RGBW/FC	20 RGBW/FC
Total light power		40W	40W	80W	100W
Lumen		R 750, G 1100, B 230, W 1600	R 500, G 740, B 160, W 1100	R 1000, G 1450, B 320, W 2200	R 1250, G 1850, B 390, W 2670
Optics		medium beam (38 mm lenses) - On request: narrow and wide beam			
Power consumption		45W	43W	87W	110W
Voltage range		Universal 100 - 240Vac			
Physical		944x93x115 mm	664x93x115 mm	1212x93x115 mm	1484x93x115 mm
Weight		4,4 Kg	-	-	-
Control		Standard interface: RS-485, Protocol: RDM / DMX 512, Artnet by external converter			
Connections		Signal: 3pin IP 67 connector (male-female) possibility to link up to 32 devices in chain Main Power: 3pin IP 67 connector (male-female) possibility to link up to 21 devices at 230V or 11 devices at 120V in chain.			
Setup		RDM Control/configuration or individually by DRS (remote control device) Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Halogen simulation CYM simulation Flicker-free function Smooth dimming function			
DMX channels		9CH mode, 6CH mode, 5CH mode, 4CH mode			



